



iALK200

PTT Portable Radio

Global PTT service via 2G/3G network
Cost-effective professional trunked features
Easy-to-deploy & Easy-to-expand network
Large coverage & less limit in capacity
IP65 with professional appearance



iTALK200 Portable Radio

KEY FEATURES AND BENEFITS

- **Global PTT service**

Users can use PTT service globally via public operator's existing mature 2G/3G network.

- **3G / GSM (GPRS) / WIFI transmission**

It provides flexible ways of using PTT service under various radio environments, if WIFI is on, WIFI will be the first choice for transmission; if WIFI is off, then 3G comes first.

- **NFC (optional) / Bluetooth**

NFC and Bluetooth function modules bring more possibilities for extended use, like guard patrol options.

- **GPS**

- **Remote programming over the air via public radio network enables lower customer maintenance cost**

Users can modify the setting for the two-way radio through web-based management platform or App in smart phone, then the modified parameters will be sent to radio via 2G/3G network automatically.

- **Remain user operation habits of critical communication**

With supporting basic functions of professional two-way radio, like voice services (all call / group call / private call / alert call etc); Text message; Tone alert (incoming call / outgoing call / text message / talk permit / low battery/emergency panic) etc.

- **Advanced signaling service**

- **Kill / stun / revive, radio monitor, ambience listening and roaming, to enable flexible management.**

- **iTALK software-Includes monitoring/recording and a unique guard patrouing system.**

- **IP65 Protection Design(Splash proof)**

SPECIFICATIONS

General

Communication Mode& Frequency Band	3G: WCDMA 850Mhz+2100Mhz or WCDMA 900Mhz+2100Mhz 2G: GSM 850M+900M+1800M+1900Mhz WIFI: 2.4Ghz
Channel Spacing	2G: 200kHz 3G: 5Mhz
Operating Temperature	-20°C ~ + 50°C
Storage Temperature	-40°C ~ + 80°C
Operating Supply	DC 3.7V
Battery	3800mAh Li-ion(standard),5000mAh Li-ion(optional)
Dimension (H*W*D) (with battery, without antenna)	115mm*54mm*30mm
Weight (with battery and antenna)	330g
Display	NA
Dustproof & Splash Waterproof	IP65

Transmitter

RF Power Output	2G: 2W ± 0.5W/3G: 0.25W ± 0.1W
Frequency Stability	±0.1 ppm
Audio Distortion	5% (typical)

Receiver

Frequency Stability	±0.1 ppm
Sensitivity	2G: BER < 0.001 when $\hat{I}_{or} = 1\mu V$; 3G: BER < 0.001 when $\hat{I}_{or} = 1\mu V$
Rated Audio Power	1W
Rated Audio Distortion	5% (typical)

STANDARD ACCESSORIES



Adapter



KBC-77Q



Battery



Antenna



Belt Clip



Kirisun Communications Co.,Ltd.

FC CE ① ISO9001:2008 Accredited Designer & Manufacturer

ADD:3-6Flrs, ROBETA Building, No.1, Qimin Road, Song Pingshan Area, Science & Industry Park, Nanshan District, Shenzhen(518057), P.R.China.

Pc: 518057

Tel: +86-755-86096076

Email: marketing.os@szkirisun.com

Http: //www.kirisun.com



RadioSource Africa CC

FC CE ① ISO9001:2008 Accredited Designer & Manufacturer

ADD:RadioSource House, 53 St Andrews Drive. Durban North, Kwa Zulu Natal South Africa

Tel: +27 31 5647727 (W)

Email: kirisun@radiosource.co.za

website: http://www.radiosource.co.za/