

RTS

DV 4475

Portable Series

Durable design, Rock Solid, easy to operate
Working frequency 400~470 Mhz 16 channels
2 Watts UHF RF output
In-built VOX function, hands-free talking
Prior scanning, in-time answer for multi-channel
Voice Inversion Scrambler
In-built CTCSS / DCS functions
BCLO
Scratch resistant
Die Cast aluminum enclosure designed for rugged outdoor use
Repeater frequency facility
Battery save function that increases battery autonomy
With 2200mAh Li-ON battery, 12Hrs for talking duration
Uses Flash memory E² prom
IP 54 - water & dust
MIL – STD 810 C, D&E

Standard Accessories



+ 400~470MHz





DV 4475 Portable Series

General	
RX and TX Frequency Range	400~470 MHZ
Frequency Control	PLL
Frequency Stability	5ppm
Channel Number	16
Channel Spacing	25 / 12.5 KHz
Power Supply	DC 3.7V 8.14WH (2200mA)
Squelch Method	Carrier wave, CTCSS, DCS
Usable Temperature Range	-10°C ~ +60°C
Louder speaker	500 mW
Dimension	117(H) x 36(D) x 60(W) mm
Weight	250 grams

Specifications are subject to change without notice due to advancements in technology.

RTS (Repeater & Trunking Systems)
 7 Charl Cilliers Street, Senekal, Free State
 South Africa
 TEL: +27 61 015 0000 / +27 61 715 0003
 Website: www.repeater.co.za

Transmitter	
Output power	2/0.5 UHF Watts
TX Current	< 1 Amp 2 watts
Modulation	FM
Audio Distortion	<5%
Audio Response	300~3000Hz(+1,-3dB)6dB/Oct
FM Noise	-40dB/12.5KHz
Harmonic	<-60dB
Max. Deviation	2.5KHz
Adjacent Channel Power	<-60dBc/12.5KHz
Start Time	<70m Sec
Time-out Timer	0-240Sec
Receiver	
Sensitivity	0.25uV(12dB SINAD EIA) 0.5uV (20dB SINAD ETS)typical
Audio Response	300-3000Hz(+1,-3dB) 6dB/Oct
Audio Power output	> 500mW @10%
FM Noise	-40dB/12.5KHz
Selectivity	>60dB/12.5KHz
Intermodulation	>60dB
spurious Rejection	>70dB

Your local Dealer